

2016

SAVE ENERGY

[<< BACK](#)

LIGHTING  
Est./Eta. 1983

# LED HERQULED 360 • E40 LAMP



Straight P&P relamping or ballast by-pass. Simply relamp 250-400W Metal Halide or Sodium HPS to LED in indoor or outdoor light fixtures, enclosed or open. Universal burning position. IP65. **Up to 18,000 lumens. 110-480V** when P&P.

[DATA SHEET \(PDF\)](#)



**HYBRID:** Autoswitching Dual Mode Driver  
**DIRECT PLUG-IN or BALLAST BY-PASS**  
Two in one: UL Type A + Type B internal driver

2016

[<< BACK](#)



# LED HERQULED • E40 LAMP



Straight P&P relamping or ballast by-pass. Simply relamp 250-400W Metal Halide or Sodium HPS to LED in open or enclosed indoor high bays, low bays and large commercial downlights. **Up to 18,000 lumens. 110-480V** when P&P.

[DATA SHEET \(PDF\)](#)



**HYBRID:** Autoswitching Dual Mode Driver  
**DIRECT PLUG-IN or BALLAST BY-PASS**  
Two in one: UL Type A + Type B internal driver

2016

[<< BACK](#)

# LED HERQULED 90 • LED LAMP



Straight P&P relamping or ballast by-pass. Simply relamp 70W-250W Metal Halide or Sodium HPS (HID) to LED in wall packs, streetlights, and parking lot lights. IP65. **Up to 8,000 lumens. 110-480V** when P&P.

[DATA SHEET \(PDF\)](#)



**HYBRID:** Autoswitching Dual Mode Driver  
**DIRECT PLUG-IN or BALLAST BY-PASS**  
Two in one: UL Type A + Type B internal driver

2016

[<< BACK](#)

# LED HERQULED HE • E40 LAMP



Highest efficiency LED lamp, up to 130LPW. Ballast By-Pass 250-400W Metal Halide or HPS (HID) lamps to LED in Indoor High Bays and Low Bays. **Up to 22,000 lumens. 110-277V or 347V** with optional step-down transformer.

[DATA SHEET \(PDF\)](#)



**INTERNAL DRIVER**  
**BALLAST BY-PASS**  
UL Type B